

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY
DEPARTMENT OF DEFENSE INDORSEMENT OF
FACTUAL ACCURACY OR OPINION

Wavelength Division Multiplexing Techniques for Enabling Complex Military Systems

Larry Lembo, James Leight, Brent Toland
TRW Space and Electronics Group, Redondo Beach, CA

DARPA/MTO Workshop on WDM for Military Platforms

April 18,2000

McLean, Virginia







The work described herein was sponsored in part by AFRL Rome Laboratory under Contract No. F30602-96-C-0026, James Nichter, COTR.

Overview

- **WDM techniques as enablers for complex military systems.**
- **Optical bandwidth is the key that unlocks the potential of photonics in military RF systems ---- low transmission loss of fiber does not carry the same weight as for commercial systems.**
- **Archetype: Large-scale phased-array antennas**
 - **Challenge: Receive-mode signal combining**
 - **Solutions:**
 - Careful optical and RF subsystem design
 - Prudent use of existing WDM technology
 - Technology developments


⇒ **Why we are here**

Phased Array Antenna Beamforming Networks: Requires Full Range of Photonics Technologies

<p>Sources</p>  <p>Candidates DFB, DBR, Nd:YAG, Ext. Cavity Tunable</p> <p>Issues/Drivers Amp/Phase Noise Multi-λ</p>	<p>Optical Switching</p>  <p>Candidates Switched Gratings, MEM's Digital Mirror, Interferometric, Fiber Optic Mechanical</p> <p>Issues/Drivers Insertion Loss, Speed, Isolation</p>
<p>Modulators</p>  <p>Candidates EAM, Mach-Zehnder, Fiber Based</p> <p>Issues/Drivers Large Bandwidth High RF Gain High Optical Power</p>	<p>Amplified Distribution</p>  <p>Candidates Talbot, Er Doped WG, Er Doped Fiber, Active Y Branch</p> <p>Issues/Drivers Splitting Losses => NF, Opt. saturation, Dynamic range System integration Amplitude control</p>
<p>True Time Delay</p>  <p>Candidates Discrete/Chirped Braggs, Opt. Switched, AWG</p> <p>Issues/Drivers Losses, Complexity, Environment</p>	<p>Photodetectors</p>  <p>Candidates PIN, Waveguide, MSM</p> <p>Issues/Drivers High Power Handling & Responsivity Bandwidth, Efficiency</p>



Signal Combining: A Critical Photonic Beamforming Issue

The need for low-loss combination of many elements while maintaining adequate amplitude control will require hybrid techniques.




Spacebased Receive Antenna: Attractive for Geosynchronous SATCOM

- **Reduced element count relative to direct radiating array**
(331 vs. 547 elements)
- **Clusters of 7 elements form beams**
via phase and amplitude weights
- **Weighting is the same for all beams**
⇒ Significant advantage for combining,
switching, redundancy






Array-Fed Reflector Beamformer with WDM Combining



Array-Feed Reflector Beamformer: WDM and Space Switching for Beam Selection

WDM routing techniques allow more efficient utilization of laser sources.



- Beamsteering may be accomplished through combination of space switching and wavelength tuning.
- Tunable, multi-wavelength, high-power, low-noise optical sources are an attractive technology.
- Integrated components (e.g., switches) needed for large-scale array packaging.

*Splitterless Optical Broadcast Switch, U.S. Patent # 5,870,216

Summary

- **WDM techniques can enhance / enable the capabilities of military systems**
- **WDM unlocks intrinsic optical bandwidth**
- **Increased bandwidth utilization enables realization of complex systems:**
 - **Large-scale phased-array / array-feed antennas**
 - **Data switching networks**
 - **Tunable delay lines**
 - **Signal processing**
- **Required technology development areas:**
 - **Novel system designs**
 - **Improved device performance**
 - **Modular integration techniques**